

# SPECIFICATIONS

The information contained herein is the exclusive property of ZK and shall not be distributed, reproduced or disclosed in whole or no in part without prior written permission of ZK

**Version : V10**

---

**Date : 2014.07.04**

---

**MODEL NAME:CT-UNITE-UR1**

---

**PRODUCT NAME :1T1R150Mbps URAT Wi-Fi Module**

---

DESIGN: \_\_\_\_\_

CHECK: \_\_\_\_\_

APPROVAL: \_\_\_\_\_

**CT UNITE COMMUNICATION TECHNOLOGY LTD**

**中科联合通信技术有限公司**

Tel:86-755-86630017 Fax:86-755-86630076

Mobile:13926580539


E-mail:zkma@zk-sz.com

[www.ctunite.com](http://www.ctunite.com)

Address: 深圳市南山区深南大道北侧佳嘉豪商务大厦6C

---

企业远景：中国无线通信模块第一品牌！

		DOCUMENT No :
REG.DATE :2011.12.2	<b>SPECIFICATION</b> MODEL NAME: <b>CT-UNITE-UR1</b>	REV.NO : 1.5
REV.DATE :2011.12.2		PAGE :2/9

## 1. Features

CT-UNITE-UR1 is the small size and low power module for IEEE 802.11b/g/n wireless LAN. CT-UNITE-UR1 is based on RT5350 solution.

IEEE 802.11 b/g/n Dual Band WLAN infrastructure

Size : 38.62mm x 23.59mm x 1.1mm

2.4GHz internal PA

Two stream spatial multiplexing up to 150Mbps

ANT (1T1R)

USB, WAN, GPIO

## 2. Ordering Information

Model	Description
CT-UNITE-UR1	Wi-Fi Module, 1T1R

## 3. Label markin



① Model No

② MAC Address BAR Code

③ MAC Address No.

④ Product Lot No. : 1110A0401

- 11 : Year


- 02 : Date

- 11 : Month

- 01 : Manufactured

- Revision No. : A

Process

		DOCUMENT No :
REG.DATE :2011.12.2	<b>S P E C I F I C A T I O N</b> MODEL NAME : <b>CT-UNITE-UR1</b>	REV.NO : 1.5
REV.DATE :2011.12.2		PAGE : 3/9

## 4. Absolute Maximum Ratings


Caution : The specifications in Table 1 define levels at which permanent damage to the device can occur. Function operation is not guaranteed under these conditions.

Operating at absolute maximum conditions for extend periods can adversely affect the long-term reliability of the device.

Parameter	Min	Max	Unit
Storage Temperature	-10	+80℃	℃
Storage Humidity (40℃)	-	90%	%

< Table 1 Absolute Maximum Ratings > . Other conditions

- 1) Do not use or store modules in the corrosive atmosphere, especially where chloride gas, sulfide gas, acid, alkali, salt or the like are contained. Also, avoid exposure to moisture.
- 2) Store the modules where the temperature and relative humidity do not exceed 5 to 40℃ and 20 to 60%.
- 3) Assemble the modules within 6 months.  
Check the soldering ability in case of 6 months over.

		DOCUMENT No :
REG.DATE :2011.12.2	<b>SPECIFICATION</b> MODEL NAME : <b>CT-UNITE-UR1</b>	REV.NO : 1.5
REV.DATE :2011.12.2		PAGE : 4/9

## 5. Operating Conditions

Parameter		Min	Typ	Max	Unit
Operating Temperature		0	-	100	°C
Operating Humidity		-	-	130	%
Supply Voltage1	VDD_3.3V	2.7	3.3	4.0	Vdc

## 6. Standard Test Conditions

The Test for electrical specification shall be performed under the following condition unless otherwise specified.

1). Ambient condition

Temperature :25°C ± 5°C

. Humidity:65% ± 5% R.H.

2). Power supply voltages

3.3V (±5%) input power at the Module


3). Current consumption over recommended range of supply voltage and operating

conditions is like below.

When it's tested, it must be supplied more than 2 times of maximal current.

# CT UNITE COMMUNICATION TECHNOLOGY LTD

1

		DOCUMENT No :
REG.DATE :2011.12.2	<b>SPECIFICATION</b> MODEL NAME : <b>CT-UNITE-UR1</b>	REV.NO : 1.5
REV.DATE :2011.12.2		PAGE : 5/9

## 7. Electrical Specifications

### 1) DC Characteristics

Current Consumption	Min.	Typ.	Max.	Unit
TX Mode ( MCS7)	-	80	-	mA
Idle and Associated state	-	40	-	
Radio disabled state	-	20	-	


### 2) RF Characteristics for IEEE802.11b ( 11Mbps mode unless otherwise specified)

Items	Contents			
Specification	IEEE802.11b			
Mode	DSSS/CCK			
Channel frequency	2400 ~ 2483 MHz			
Data rate	1,2,5.5,11Mbps			
<b>TX Characteristics</b>	<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	<b>Unit</b>
Power Level	16	17	18	dBm
Spectrum Mask				
1 <sup>st</sup> side lobes ( to fc ±11MHz)	-	-43	-30	dBr
2 <sup>nd</sup> side lobes ( to fc ±22MHz)	-	-58	-50	dBr
Modulation Accuracy (EVM)	-	30	30	%
Power On/Off ramp	-	0.5	2.0	Usec
Freq. Tolerance	-15	-	15	ppm
Chip Clock Freq. Tolerance	-15	-	15	ppm
<b>RX Characteristics</b>	<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	<b>Unit</b>
Minimum Input Level Sens (FER ≤ 8%)	-	-88	-76	dBm
Maximum Input Level (FER ≤ 8%)	-10	-	-	dBm

\* Normal Condition : 25°C, VDD=3.3/5V.

# CT UNITE COMMUNICATION TECHNOLOGY LTD

1

		DOCUMENT No :
REG.DATE :2011.12.2	<b>SPECIFICATION</b> MODEL NAME : <b>CT-UNITE-UR1</b>	REV.NO : 1.5
REV.DATE :2011.12.2		PAGE :6/9


### 3) RF Characteristics for IEEE802.11g ( 54Mbps mode unless otherwise specified)

Items	Contents			
Specification	IEEE802.11g			
Mode	OFDM			
Channel frequency	2400 ~ 2483 MHz			
Data rate	6,9,12,18,24,36,48,54Mbps			
<b>TX Characteristics</b>	<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	<b>Unit</b>
Power Level	14	15	16	dBm
Spectrum Mask				
at fc ±11MHz	-	-32	-20	dBr
at fc ±20MHz	-	-43	-28	dBr
at fc ≥ ± 30MHz	-	-48	-40	dBr
Constellation Error (EVM)	-	-34	-25	dB
Freq. Tolerance	-15	-	15	ppm
Chip Clock Freq. Tolerance	-15	-	15	ppm
<b>RX Characteristics</b>	<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	<b>Unit</b>
Minimum Input Level Sens. (PER ≤ 10%)	-	-75		ppm
Maximum Input Level (PER ≤ 10%)	-20	-		ppm

\*Normal Condition : 25°C, VDD=3.3/5V

# CT UNITE COMMUNICATION TECHNOLOGY LTD

1

		DOCUMENT No :
REG.DATE :2011.12.2	<b>SPECIFICATION</b> MODEL NAME : <b>CT-UNITE-UR1</b>	REV.NO : 1.5
REV.DATE :2011.12.2		PAGE :7/9

### 3) RF Characteristics for IEEE802.11n ( 54Mbps mode unless otherwise specified)

Items	Contents			
Specification	IEEE802.11n			
Mode	OFDM			
Channel frequency	2400 ~ 2483 MHz			
Data rate	6,9,12,18,24,36,48,54Mbps			
<b>TX Characteristics</b>	<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	<b>Unit</b>
Power Level	13	14	15	dBm
Spectrum Mask				
at fc ±11MHz	-	-32	-20	dBr
at fc ±20MHz	-	-43	-28	dBr
at fc ≥ ± 30MHz	-	-48	-40	dBr
Constellation Error (EVM)	-	-34	-25	dB
Freq. Tolerance	-15	-	15	ppm
Chip Clock Freq. Tolerance	-15	-	15	ppm
<b>RX Characteristics</b>	<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	<b>Unit</b>
Minimum Input Level Sens. (PER ≤ 10%)	-	-75		ppm
Maximum Input Level (PER ≤ 10%)	-20	-		ppm

\*Normal Condition : 25°C, VDD=3.3/5V



DOCUMENT No :

REG.DATE :2011.12.2

**SPECIFICATION**  
MODEL NAME : **CT-UNITE-UR1**

REV.NO : 1.5

REV.DATE :2011.12.2

PAGE :8/9

## 8. Pin Description

Terminal No	Terminal name	Network name	Terminal Voltage	Signal Type
1		I2C_SCLK		
2		I2C_SD		
3		GPIO5	I/O	
4		GPIO3	I/O	
5		GND		
6		GND		
7		GND		
8		GND		
9		GND		
10		GND		
11		GND		
12		GND		
13		GND		
14		GND		
15		GND		
16		WLAN_LED		
17		TXD2		
18		RXD2		
19		USB_DM		
20		USB_DP		
21		REST		
22		TXD		
23		RXD		
24		3_3VD		VCC33
25		GND		GND
26		WPS		
27		WAN_RX+		
28		WAN_RX-		
29		WAN_TX+		
30		WAN_TX-		





DOCUMENT No :

REG.DATE :2011.12.2

**SPECIFICATION**  
MODEL NAME : **CT-UNITE-UR1**

REV.NO : 1.5

REV.DATE :2011.12.2

PAGE : 8/9

## 8. Pin Description

